



NTNY BEARING LTD



35 mm x 100 mm x 25 mm skf 6407 bearing

Bearing No. 6407

Size	35x100x25 mm
Bore Diameter	35 mm
Outer Diameter	100 mm
Width	25 mm
d	35 mm
D	100 mm
B	25 mm
C	25 mm
d1	57,4 mm
r1 min.	1,5 mm
r2 min.	1,5 mm
D1	79,6 mm
D2	– mm
da min.	46 mm
Da max.	89 mm
rc max.	1,5 mm
Weight	0,97 Kg
Basic dynamic load rating (C)	55,3 kN
Basic static load rating (C0)	31 kN
Fatigue load limit (Pu)	1,29
Reference speed	16000 r/min
Limiting speed	10000 r/min
Calculation factor (f0)	12
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF

6407 Bearing 2D drawings and 3D CAD models



NTNY BEARING LTD

Minimum Buy Quantity	N/A
Weight / Kilogram	0.98
EAN	7316576621031
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	35MM Bore; 100MM Outside Diameter; 25MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6407
Weight / LBS	2.16
Bore	1.378 Inch 35 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Outer Race Width	0.984 Inch 25 Millimeter
bore diameter:	35 mm
static load capacity:	31 kN



NTNY BEARING LTD

outside diameter:	100 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	25 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	25 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1.5 mm
snap ring included:	Without Snap Ring
maximum rpm:	10000 RPM
internal clearance:	C0
series:	64
dynamic load capacity:	55.3 kN
d_1	57.45 mm
D_1	79.55 mm
$r_{1,2}$ min.	1.5 mm
d_a min.	46 mm
D_a max.	89 mm
r_a max.	1.5 mm
Basic dynamic load rating C	55.3 kN
Basic static load rating C_0	31 kN
Fatigue load limit P_u	1.29 kN
Calculation factor k_r	0.035
Calculation factor f_0	12.1
Mass bearing	0.97 kg