



# NTNY BEARING LTD



55 mm x 120 mm x 29 mm skf 7311 becbm bearing

Bearing No. 7311 becbm

7311 becbm Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	22.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.5
EAN	7316576634383
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	55MM Bore; 120MM Outside Diameter; 29MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap



# NTNY BEARING LTD

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7311 BECBM
Weight / LBS	3.294
d	2.165 Inch   55 Millimeter
B	1.142 Inch   29 Millimeter
D	4.724 Inch   120 Millimeter
bore diameter:	55 mm
radial static load capacity:	60 kN
outside diameter:	120 mm
cage material:	Brass
overall width:	29 mm
outer ring width:	29 mm
contact angle:	40 °
maximum rpm:	7000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2 mm
radial dynamic load capacity:	85 kN
series:	73
d	55 mm



## NTNY BEARING LTD

D	120 mm
B	29 mm
d <sub>1</sub>	80.3 mm
d <sub>2</sub>	66.66 mm
D <sub>1</sub>	96.6 mm
a	51 mm
r <sub>1,2</sub> min.	2 mm
r <sub>3,4</sub> min.	1 mm
d <sub>a</sub> min.	66 mm
D <sub>a</sub> max.	109 mm
D <sub>b</sub> max.	114 mm
r <sub>a</sub> max.	2 mm
r <sub>b</sub> max.	1 mm
Basic dynamic load rating C	85 kN
Basic static load rating C <sub>0</sub>	60 kN
Fatigue load limit P <sub>u</sub>	2.55 kN
Reference speed	7000 r/min
Limiting speed	9000 r/min
Calculation factor A	0.0574
Calculation factor k <sub>r</sub>	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y <sub>0</sub>	0.26
Calculation factor Y <sub>2</sub>	0.57
Calculation factor X	0.57
Calculation factor Y <sub>0</sub>	0.52
Calculation factor Y <sub>1</sub>	0.55
Calculation factor Y <sub>2</sub>	0.93
Mass bearing	1.4 kg