



NTNY BEARING LTD



130 mm x 165 mm x 18 mm skf 61826 bearing

Bearing No. 61826

61826 Bearing 2D drawings and 3D CAD models

| | |
|---|--------------------------|
| Size | 165x130x18 mm |
| Bore Diameter | 165 mm |
| Outer Diameter | 130 mm |
| Width | 18 mm |
| d | 130 mm |
| D | 165 mm |
| B | 18 mm |
| d ₁ | 140 mm |
| D ₂ | 157.7 mm |
| r _{1,2} - min. | 1.1 mm |
| d _a - min. | 136 mm |
| D _a - max. | 159 mm |
| r _a - max. | 1 mm |
| Basic dynamic load rating - C | 37.7 kN |
| Basic static load rating - C ₀ | 43 kN |
| Fatigue load limit - P _u | 1.6 kN |
| Reference speed | 8000 r/min |
| Limiting speed | 4800 r/min |
| Calculation factor - k _r | 0.015 |
| Calculation factor - f ₀ | 16.1 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.813 |



NTNY BEARING LTD

| | |
|---------------------------------|--|
| EAN | 7316576612992 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 130MM Bore; 165MM Outside Diameter; 18MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 61826 |
| Weight / LBS | 1.79 |
| Bore | 5.118 Inch 130 Millimeter |
| Outer Race Width | 0.709 Inch 18 Millimeter |
| Outside Diameter | 6.496 Inch 165 Millimeter |
| bore diameter: | 130 mm |
| static load capacity: | 43 kN |
| outside diameter: | 165 mm |
| precision rating: | Not Rated |
| | |



NTNY BEARING LTD

| | |
|--------------------------------|--------------------------|
| overall width: | 18 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Open |
| outer ring width: | 18 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| fillet radius: | 1 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm: | 4800 RPM |
| internal clearance: | C0 |
| series: | 61 |
| dynamic load capacity: | 37.7 kN |
| d_1 | 140 mm |
| D_2 | 157.7 mm |
| $r_{1,2}$ min. | 1.1 mm |
| d_a min. | 136 mm |
| D_a max. | 159 mm |
| r_a max. | 1 mm |
| Basic dynamic load rating C | 37.7 kN |
| Basic static load rating C_0 | 43 kN |
| Fatigue load limit P_u | 1.6 kN |
| Calculation factor k_r | 0.015 |
| Calculation factor f_0 | 16.1 |
| Mass bearing | 0.75 kg |