



NTNY BEARING LTD



60 mm x 85 mm x 13 mm skf 61912 bearing

Bearing No. 61912

| | |
|---|--------------------------|
| Size | 85x60x13 mm |
| Bore Diameter | 85 mm |
| Outer Diameter | 60 mm |
| Width | 13 mm |
| d | 60 mm |
| D | 85 mm |
| B | 13 mm |
| d ₁ | 68.3 mm |
| D ₂ | 78.7 mm |
| r _{1,2} - min. | 1 mm |
| d _a - min. | 64.6 mm |
| D _a - max. | 80.4 mm |
| r _a - max. | 1 mm |
| Basic dynamic load rating - C | 16.5 kN |
| Basic static load rating - C ₀ | 12 kN |
| Fatigue load limit - P _u | 0.6 kN |
| Reference speed | 16000 r/min |
| Limiting speed | 10000 r/min |
| Calculation factor - k _r | 0.02 |
| Calculation factor - f ₀ | 13.9 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.22 |

61912 Bearing 2D drawings and 3D CAD models



NTNY BEARING LTD

| | |
|---------------------------------|--|
| EAN | 7316577121998 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 60MM Bore; 85MM Outside Diameter; 13MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 61912 |
| Weight / LBS | 0.48 |
| Outside Diameter | 3.346 Inch 85 Millimeter |
| Outer Race Width | 0.512 Inch 13 Millimeter |
| Bore | 2.362 Inch 60 Millimeter |
| bore diameter: | 60 mm |
| static load capacity: | 14.3 kN |
| outside diameter: | 85 mm |
| precision rating: | Not Rated |
| | |



NTNY BEARING LTD

| | |
|--------------------------------|--------------------------|
| overall width: | 13 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Open |
| outer ring width: | 13 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| fillet radius: | 1 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm: | 10000 RPM |
| internal clearance: | C0 |
| series: | 61 |
| dynamic load capacity: | 16.5 kN |
| d_1 | 68.3 mm |
| D_2 | 78.7 mm |
| $r_{1,2}$ min. | 1 mm |
| d_a min. | 64.6 mm |
| D_a max. | 80.4 mm |
| r_a max. | 1 mm |
| Basic dynamic load rating C | 16.5 kN |
| Basic static load rating C_0 | 12 kN |
| Fatigue load limit P_u | 0.6 kN |
| Calculation factor k_r | 0.02 |
| Calculation factor f_0 | 13.9 |
| Mass bearing | 0.2 kg |