



# NTNY BEARING LTD



40 mm x 80 mm x 18 mm skf 7208 becbp bearing

Bearing No. 7208 becbp

7208 becbp Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.36
EAN	7316576632983
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap



## NTNY BEARING LTD

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7208 BECBP
Weight / LBS	0.785
d	1.575 Inch   40 Millimeter
B	0.709 Inch   18 Millimeter
D	3.15 Inch   80 Millimeter
bore diameter:	40 mm
radial static load capacity:	26 kN
outside diameter:	80 mm
cage material:	Nylon
overall width:	18 mm
outer ring width:	18 mm
contact angle:	40 °
maximum rpm:	11000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	36.5 kN
series:	72
d	40 mm



## NTNY BEARING LTD

D	80 mm
B	18 mm
d <sub>1</sub>	56.25 mm
d <sub>2</sub>	48.08 mm
D <sub>1</sub>	65.55 mm
a	34 mm
r <sub>1,2</sub> min.	1.1 mm
r <sub>3,4</sub> min.	0.6 mm
d <sub>a</sub> min.	47 mm
D <sub>a</sub> max.	73 mm
D <sub>b</sub> max.	75.8 mm
r <sub>a</sub> max.	1 mm
r <sub>b</sub> max.	0.6 mm
Basic dynamic load rating C	36.5 kN
Basic static load rating C <sub>0</sub>	26 kN
Fatigue load limit P <sub>u</sub>	1.1 kN
Reference speed	10000 r/min
Limiting speed	11000 r/min
Calculation factor A	0.0102
Calculation factor k <sub>r</sub>	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y <sub>0</sub>	0.26
Calculation factor Y <sub>2</sub>	0.57
Calculation factor X	0.57
Calculation factor Y <sub>0</sub>	0.52
Calculation factor Y <sub>1</sub>	0.55
Calculation factor Y <sub>2</sub>	0.93
Mass bearing	0.37 kg