



NTNY BEARING LTD



55 mm x 120 mm x 29 mm skf nu 311 ecp bearing

Bearing No. nu 311 ecp

nu 311 ecp Bearing 2D drawings and 3D CAD models

Size	120x55x29 mm
Bore Diameter	120 mm
Outer Diameter	55 mm
Width	29 mm
d	55 mm
D	120 mm
B	29 mm
D ₁	100.3 mm
F	70.5 mm
r _{1,2} - min.	2 mm
r _{3,4} - min.	2 mm
s	2 mm
d _a - min.	65 mm
d _a - max.	68 mm
d _b - min.	73 mm
D _a - max.	109.2 mm
r _a - max.	2 mm
r _b - max.	2 mm
Basic dynamic load rating - C	156 kN
Basic static load rating - C ₀	143 kN
Fatigue load limit - P _u	18.6 kN
Reference speed	6000 r/min
Limiting speed	7000 r/min
Calculation factor - k _r	0.15



NTNY BEARING LTD

Category	Cylindrical Roller Bearings
Inventory	3.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.472
EAN	7316576616129
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	55MM Bore; Straight Bore Profile; 120MM Outside Diameter; 29MM Width; Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium In
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing



NTNY BEARING LTD

Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 311 ECP
Weight / LBS	3.243
Bore	2.165 Inch 55 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Width	1.142 Inch 29 Millimeter
bore diameter:	55 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	120 mm
maximum rpm:	7000 RPM
overall width:	29 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C0
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	29 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	156 kN
series:	NU3
static load capacity:	143 kN
D ₁	100.3 mm
r _{1,2} min.	2 mm



NTNY BEARING LTD

$r_{3,4}$ min.	2 mm
s max.	2 mm
d_a min.	65 mm
d_a max.	68 mm
d_b min.	73 mm
D_a max.	109.2 mm
r_a max.	2 mm
r_b max.	2 mm
Basic dynamic load rating C	156 kN
Basic static load rating C_0	143 kN
Fatigue load limit P_u	18.6 kN
Calculation factor k_r	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	1.44 kg
Angle ring	HJ 311 EC