




NTNY BEARING LTD



50 mm x 90 mm x 20 mm skf 7210 becbp bearing

Bearing No. 7210 becbp

7210 becbp Bearing 2D drawings and 3D CAD models

Size	90x50x20 mm
Bore Diameter	90 mm
Outer Diameter	50 mm
Width	20 mm
d	50 mm
D	90 mm
B	20 mm
d ₁	65.75 mm
d ₂	57.68 mm
D ₁	75.15 mm
a	39 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
d _a - min.	57 mm
D _a - max.	83 mm
D _b - max.	85.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	40 kN
Basic static load rating - C ₀	31 kN
Fatigue load limit - P _u	1.3 kN
Reference speed	9000 r/min
Limiting speed	9000 r/min
Calculation factor - k _r	0.095



NTNY BEARING LTD

Calculation factor - k_a	1.4
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.45
EAN	7316577292193
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric



NTNY BEARING LTD

Long Description	50MM Bore; 90MM Outside Diameter; 20MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7210 BECBP
Weight / LBS	0.999
Outside Diameter	3.543 Inch 90 Millimeter
Width	0.787 Inch 20 Millimeter
Bore	1.969 Inch 50 Millimeter
bore diameter:	50 mm
radial static load capacity:	31 kN
outside diameter:	90 mm
cage material:	Nylon
overall width:	20 mm
outer ring width:	20 mm
contact angle:	40 °
maximum rpm:	9000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1 mm



NTNY BEARING LTD

radial dynamic load capacity:	40 kN
series:	72
d_1	65.75 mm
d_2	57.68 mm
D_1	75.15 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	57 mm
D_a max.	83 mm
D_b max.	85.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	40 kN
Basic static load rating C_0	31 kN
Fatigue load limit P_u	1.32 kN
Calculation factor A	0.014
Calculation factor k_r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.47 kg