



NTNY BEARING LTD



12 mm x 32 mm x 10 mm skf 7201 becbp bearing

Bearing No. 7201 becbp

7201 becbp Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.039
EAN	7316576649684
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap



NTNY BEARING LTD

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7201 BECBP
Weight / LBS	0.079
B	0.394 Inch 10 Millimeter
d	0.472 Inch 12 Millimeter
D	1.26 Inch 32 Millimeter
bore diameter:	12 mm
radial static load capacity:	3.8 kN
outside diameter:	32 mm
cage material:	Nylon
overall width:	10 mm
outer ring width:	10 mm
contact angle:	40 °
maximum rpm:	26000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	0.6 mm
radial dynamic load capacity:	7.61 kN
series:	72
d	12 mm



NTNY BEARING LTD

D	32 mm
B	10 mm
d ₁	20.2 mm
d ₂	16.57 mm
D ₁	25 mm
a	14 mm
r _{1,2} min.	0.6 mm
r _{3,4} min.	0.3 mm
d _a min.	16.2 mm
D _a max.	27.8 mm
D _b max.	30 mm
r _a max.	0.6 mm
r _b max.	0.3 mm
Basic dynamic load rating C	7.61 kN
Basic static load rating C ₀	3.8 kN
Fatigue load limit P _u	0.16 kN
Reference speed	28000 r/min
Limiting speed	26000 r/min
Calculation factor A	0.000283
Calculation factor k _r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y ₀	0.26
Calculation factor Y ₂	0.57
Calculation factor X	0.57
Calculation factor Y ₀	0.52
Calculation factor Y ₁	0.55
Calculation factor Y ₂	0.93
Mass bearing	0.036 kg